

Model	Specification	Gizmoz Formula 61" Petrol F6127KH-EU	Gizmoz Formula 61" Diesel F6127DI-EU	Gizmoz Formula 61" LPG F6127LPG-EU	Gizmoz Formula 52" Diesel F5223DI-EU	
Engine	Model	Kohler 27HP/ES V-Twin	Briggs Vanguard DM950D	Kohler 27HP/ES V-Twin	Vanguard D850	
	No of cylinders	2	3	2	3	
	Max Horsepower KW (HP)	20 KW(27HP)	20 KW(27HP)	20 KW(27HP)	17 KW(23HP)	
	Cubic capacity	725	950	725	850	
	Starting system	Key Switch	Key Switch	Key Switch	Key Switch	
	Engine Stop	Key and OPC	Key and OPC	Key and OPC	Key and OPC	
	Battery Voltage	12v	12v	12v	12v	
	Engine Oil capacity / type	1.8 litres /10W30	3 litres	1.8 litres /10W30	3 litres	
	Fuel tank capacity	37litres	37litres	37litres	37litres	
	Dimensions	Overall Length	2134 mm	2235mm	2134 mm	2134 mm
Overall Width		1600 mm	1600 mm	1600 mm	1370	
Overall Height (Ex ROPS)		1900mm (1200 mm)	1900mm (1200 mm)	1900mm (1200 mm)	1900mm (1200 mm)	
Turning Radius		Zero turning radius (ZTR)	Zero turning radius (ZTR)	Zero turning radius (ZTR)	Zero turning radius (ZTR)	
Weight (Ex ROPS)		700 kg (680kg)	800 kg (780kg)	800 kg (780kg)	800 kg (780kg)	
Wheel Base		1296 mm	1372mm	1296 mm	1296 mm	
Tyre Size - Front		13 x 5.00 - 6	13 x 5.00 - 6	13 x 5.00 - 6	13 x 5.00 - 6	
Tyre Size - Rear		24 x 12.00 - 12	24 x 12.00 - 12	24 x 12.00 - 12	24 x 12.00 - 12	
Transmission		Transmission system	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
		Speed Control	Patented speed sensitive steering	Patented speed sensitive steering	Patented speed sensitive steering	Patented speed sensitive steering
	Forward speed range	0 - 16 Kmh	0 - 16 Kmh	0 - 16 Kmh	0 - 16 Kmh	
	Reverse Speed range	0 - 8 Kmh	0 - 8 Kmh	0 - 8 Kmh	0 - 8 Kmh	
	Hydraulic Pumps	Hydrogear	Hydrogear	Hydrogear	Hydrogear	
	Wheel Motors	Hydrogear	Hydrogear	Hydrogear	Hydrogear	
	Hydraulic Oil capacity / type	3.3litres Mobil 1 5-W-50	3.3litres Mobil 1 5-W-50	3.3litres Mobil 1 5-W-50	3.3litres Mobil 1 5-W-50	
	Brake Type	External expanding shoe	External expanding shoe	External expanding shoe	External expanding shoe	
	PTO Clutch	Borg Warner	Borg Warner	Borg Warner	Borg Warner	
	Features	ROPS (Folding)	Optional	Optional	Optional	Optional
Adjustable suspension seat		Standard	Standard	Standard	Optional	
Kevlar belts		Standard	Standard	Standard	Standard	
Horn		Standard	Standard	Standard	Standard	
Amber Beacon		Optional	Optional	Optional	Optional	
Road lighting kit		Optional	Optional	Optional	Optional	
Hour Meter / Tachometer		Standard	Optional	Standard	Standard	
Fuel tank guards		Standard	Standard	Standard	Standard	
Cup Holder		Standard	Standard	Standard	Standard	
Front Fender & Lashing post		Optional	Optional	Optional	Optional	
Mower Specification	Tool Box	Standard	Optional	Standard	Optional	
	Paint finish	Power coat with E-Coat primer	Power coat with E-Coat primer	Power coat with E-Coat primer	Power coat with E-Coat primer	
	Construction	4.5 mm (7 Gauge) Steel	4.5 mm (7 Gauge) Steel	4.5 mm (7 Gauge) Steel	4.5 mm (7 Gauge) Steel	
	Mower lift system	Electronic	Manual with Spring assist	Electronic	Manual with Spring assist	
	Mounting system of mower deck	Parallel linkage	Parallel linkage	Parallel linkage	Parallel linkage	
	Blade Drive method	Hexagonal Kevlar Belt	Hexagonal Kevlar Belt	Hexagonal Kevlar Belt	Kevlar V section Belt	
	Belt tensioning	Automatic	Automatic	Automatic	Automatic	
	Adjustment of cutting height	Infinitely variable	15mm increments	Infinitely variable	15mm increments	
	Cutting width	1550 mm	1550 mm	1550 mm	1320mm	
	Cutting height	25 mm - 145 mm	25 mm - 145 mm	25 mm - 145 mm	25 mm - 145 mm	
No of Blades	3 Marbain steel (Contra-rotating)	3 Marbain steel (1 Contra-rotating)	3 Marbain steel (Contra-rotating)	3 Marbain steel		
Spindles	25.4mm Shaft - Greased, vented, Ball Bearings	25.4mm Shaft - Greased, vented, Ball Bearings	25.4mm Shaft - Greased, vented, Ball Bearings	25.4mm Shaft - Greased, vented, Ball Bearings		
Discharge	Rear	Rear	Rear	Side		
Anti-scalp wheels	360 degree catoring	360 degree catoring	360 degree catoring	Fixed		
Mulch Kit	Optional	Optional	Optional	Optional		

\*Whilst every effort has been made to ensure up to date and accurate information, the company reserves the right to change the above specification without notice  
This brochure is for descriptive purposes only. Please contact your Gizmoz dealer for warranty information

Model	Specification	Gizmo 48" Formula - "Steered ZTR" F4823DI-EU	
Engine	Model	Vanguard D850	
	No of cylinders	3	
	Max Horsepower KW (HP)	17 KW(23HP)	
	Cubic capacity	850	
	Starting system	Key Switch	
	Engine Stop	Key and OPC	
	Battery Voltage	12v	
	Engine Oil capacity / type	3 litres	
	Fuel tank capacity	37litres	
	Dimensions	Overall Length	2235mm
Overall Width		1260mm	
Overall Height (Ex ROPS)		1900mm (1200 mm)	
Turning Radius		Zero turning radius (ZTR)	
Weight (Ex ROPS)		730kg(710kg)	
Wheel Base		1372mm	
Tyre Size - Front		13 x 5.00 - 6	
Tyre Size - Rear		23 x 9.5 -12	
Transmission		Transmission system	Hydrostatic
		Speed Control	Patented speed sensitive steering
	Forward speed range	0 - 16 Kmh	
	Reverse Speed range	0 - 8 Kmh	
	Hydraulic Pumps	Hydrogear	
	Wheel Motors	Hydrogear	
	Hydraulic Oil capacity / type	3.3litres Mobil 1 5-W-50	
	Brake Type	External expanding shoe	
	PTO Clutch	Borg Warner	
	Features	ROPS (Folding)	Optional
Adjustable suspension seat		Optional	
Kevlar belts		Standard	
Horn		Standard	
Amber Beacon		Optional	
Road lighting kit		Optional	
Hour Meter / Tachometer		Standard	
Fuel tank guards		Standard	
Cup Holder		Standard	
Front Fender & Lashing post		Optional	
Tool Box		Optional	
Paint finish		Power coat with E-Coat primer	
Mower Specification		Construction	4.5 mm (7 Gauge) Steel
		Mower lift system	Manual with Spring assist
		Mounting system of mower	Parallel linkage
	Blade Drive method	Kevlar V section Belt	
	Belt tensioning	Automatic	
	Adjustment of cutting height	15mm increments	
	Cutting width	1200mm	
	Cutting height	25 mm - 145 mm	
	No of Blades	3 Marbain steel	
	Spindles	25.4mm Shaft - Greased, vented, Ball Bearings	
	Discharge	Rear	
	Anti-scalp wheels	Fixed	
	Mulch Kit	Optional	

Model	Specification	Gizmo Classic 52" Diesel CL5223DI-EU	
Engine	Model	Vanguard D850	
	No of cylinders	3	
	Max Horsepower KW (HP)	17 KW(23HP)	
	Cubic capacity	850	
	Starting system	Key Switch	
	Engine Stop	Key and OPC	
	Battery Voltage	12v	
	Engine Oil capacity / type	3 litres	
	Fuel tank capacity	37litres	
	Dimensions	Overall Length	2235mm
Overall Width		1370	
Overall Height (Ex ROPS)		1900mm (1200 mm)	
Turning Radius		Zero turning radius (ZTR)	
Weight (Ex ROPS)		635kg (615kg)	
Wheel Base		1372mm	
Tyre Size - Front		13 x 5.00 - 6	
Tyre Size - Rear		23 x 9.5 -12	
Transmission		Transmission system	Hydrostatic
		Speed Control	Twin centre sticks
	Forward speed range	0 - 16 Kmh	
	Reverse Speed range	0 - 8 Kmh	
	Hydraulic Pumps	Hydrogear	
	Wheel Motors	Hydrogear	
	Hydraulic Oil capacity / type	3.3litres Mobil 1 5-W-50	
	Brake Type	External expanding shoe	
	PTO Clutch	Borg Warner	
	Features	ROPS (Folding)	Optional
Adjustable suspension seat		Optional	
Kevlar belts		Standard	
Horn		Standard	
Amber Beacon		Optional	
Road lighting kit		Optional	
Hour Meter / Tachometer		Standard	
Fuel tank guards		Standard	
Cup Holder		Standard	
Front Fender & Lashing post		Optional	
Tool Box		Optional	
Paint finish		Power coat with E-Coat primer	
Mower Specification		Construction	4.5 mm (7 Gauge) Steel
		Mower lift system	Manual with Spring assist
		Mounting system of mower	Parallel linkage
	Blade Drive method	Kevlar V section Belt	
	Belt tensioning	Automatic	
	Adjustment of cutting height	15mm increments	
	Cutting width	1320mm	
	Cutting height	25 mm - 145 mm	
	No of Blades	3 Marbain steel	
	Spindles	25.4mm Shaft - Greased, vented, Ball Bearings	
	Discharge	Rear	
	Anti-scalp wheels	Fixed	
	Mulch Kit	Optional	

Model	Specification	Gizmo Classic 48" Diesel CL4823DI-EU	
Engine	Model	Vanguard D850	
	No of cylinders	3	
	Max Horsepower KW (HP)	17 KW(23HP)	
	Cubic capacity	850	
	Starting system	Key Switch	
	Engine Stop	Key and OPC	
	Battery Voltage	12v	
	Engine Oil capacity / type	3 litres	
	Fuel tank capacity	37litres	
	Dimensions	Overall Length	2235mm
Overall Width		1260mm	
Overall Height (Ex ROPS)		1900mm (1200 mm)	
Turning Radius		Zero turning radius (ZTR)	
Weight (Ex ROPS)		635kg (615kg)	
Wheel Base		1372mm	
Tyre Size - Front		13 x 5.00 - 6	
Tyre Size - Rear		23 x 9.5 -12	
Transmission		Transmission system	Hydrostatic
		Speed Control	Twin centre sticks
	Forward speed range	0 - 16 Kmh	
	Reverse Speed range	0 - 8 Kmh	
	Hydraulic Pumps	Hydrogear	
	Wheel Motors	Hydrogear	
	Hydraulic Oil capacity / type	3.3litres Mobil 1 5-W-50	
	Brake Type	External expanding shoe	
	PTO Clutch	Borg Warner	
	Features	ROPS (Folding)	-
Adjustable suspension seat		Optional	
Kevlar belts		Standard	
Horn		Standard	
Amber Beacon		Optional	
Road lighting kit		Optional	
Hour Meter / Tachometer		Standard	
Fuel tank guards		Standard	
Cup Holder		Standard	
Front Fender & Lashing post		Optional	
Tool Box		Optional	
Paint finish		Power coat with E-Coat primer	
Mower Specification		Construction	4.5 mm (7 Gauge) Steel
		Mower lift system	Manual with Spring assist
		Mounting system of mower	Parallel linkage
	Blade Drive method	Kevlar V section Belt	
	Belt tensioning	Automatic	
	Adjustment of cutting height	15mm increments	
	Cutting width	1200mm	
	Cutting height	25 mm - 145 mm	
	No of Blades	3 Marbain steel	
	Spindles	25.4mm Shaft - Greased, vented, Ball Bearings	
	Discharge	Rear	
	Anti-scalp wheels	Fixed	
	Mulch Kit	Optional	

\*Whilst every effort has been made to ensure up to date and accurate information, this brochure is for descriptive purposes only. Please contact your Gizmo dealer for more information.